



US005668778A

77364

United States Patent [19]**Quazi**[11] **Patent Number:** **5,668,778**[45] **Date of Patent:** **Sep. 16, 1997**

[54] **METHOD FOR DETECTING ACOUSTIC SIGNALS FROM AN UNDERWATER SOURCE**

[75] **Inventor:** **Azizul H. Quazi**, East Lyme, Conn.

[73] **Assignee:** **The United States of America as represented by the Secretary of the Navy**, Washington, D.C.

[21] **Appl. No.:** **677,205**

[22] **Filed:** **Jul. 9, 1996**

[51] **Int. Cl.⁶** **H04B 1/06**

[52] **U.S. Cl.** **367/135; 367/98; 367/131**

[58] **Field of Search** **367/135, 136, 367/124, 98, 87, 131; 395/2.09; 364/423**

[56] **References Cited**

U.S. PATENT DOCUMENTS

5,243,686 9/1993 Tokuda et al. 395/2.09

Primary Examiner—Daniel T. Pihulic

Attorney, Agent, or Firm—Michael J. McGowan; Prithvi C. Lall; Michael F. Oglo

[57] **ABSTRACT**

A method for detecting radiated and reflected acoustic signals from an underwater source, wherein the acoustic signals are present in a random noise environment and form an output therewith. The method includes the steps of operating an entropy-based acoustic receiver to receive the output, calculating the entropy of the received output, and comparing the calculated entropy with a selected entropy threshold value. A substantial difference is indicative of the presence of an acoustic signal from an underwater source. A less than substantial difference is indicative of a lack of presence of an acoustic signal from an underwater source.

5 Claims, 2 Drawing Sheets